

Leica Jogger Series Automatic Levels – Fit for Work



SITE PROOF
by Leica Geosystems

- when it has to be **right**

Leica
Geosystems

Leica Jogger Series

Automatic Levels – Fit for Work



**Building and
Civil Engineering**



Profiling



Landscaping



Area Levelling

The Leica Jogger Series is the ideal partner for all your daily levelling tasks.

Fit for Work – Great features and great performance

- Choice of magnification: 20x/24x/28x or 32x
- Automatic, air-damped compensator
- Smooth, double-sided endless fine drive for easy and precise targeting
- Horizontal circle with 360° division



Fit for Work – Quality and Endurance

- Water resistant (IP54) for instrument use under harsh environmental conditions
- 1 year warranty and access to the worldwide Leica Geosystems network of service and support centres

Fit for Work – Great Jogger package

Tripod and staff are important parts of any levelling equipment. Get better results with approved original Leica Geosystems tripods and staffs. Ask for the original Leica Jogger package.



| Leica Jogger | 20 | 24 | 28 | 32 |
|--|----------------|--------|------|------|
| Standard deviation per 1 km double-run levelling | 2.5 mm | 2.0 mm | | |
| Telescope | | | | |
| Telescope image | upright | | | |
| Magnification | 20 x | 24 x | 28 x | 32 x |
| Clear objective lens | 36 mm | | | |
| Shortest focusing distance | < 1.0 m | | | |
| Field of view at 100 m | < 2.1 m | | | |
| Multiplication constant | 100 | | | |
| Additive constant | 0 | | | |
| Compensator | | | | |
| Working range | ± 15' | | | |
| Setting accuracy (standard deviation) | < 0.5" | | | |
| Circular bubble | 8'/2 mm | | | |
| Horizontal circle | | | | |
| Graduation | 360° | | | |
| Interval | 1° | | | |
| Weight (net) | 1.5 kg | | | |
| Operating temperature range | -20°C to +40°C | | | |

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2010. 784684en – XII.10 – RDV